



## Serve-over DOLPHIN



### Product categories



### Technical features







DOLPHIN				
Length mm		1250	1875	2500
DOLPHIN	SCR (without Glass)	•	•	•
	RCB	•	•	•
Display area m2		0.98		
Loading area m2		1.19		




SCR With "serpentino" SCR Non refrigerated




SCR With evaporator SCR With "serpentino" + Evaporator



LS With "serpentino" LS Non refrigerated




RCB With "serpentino" RCB Non refrigerated






RCB With evaporator RCB With "serpentino" + Evaporator



LS With evaporator LS With "serpentino" + Evaporator





## Legend

 Meat	 Chicken	 Fish	 Pre-packed fish
 Delicatessen	 Cheese	 Dairy products	 Gastronomy
 Pastries	 Pre-packed fruit and vegetables	 Fruits and Vegetables	 Sandwiches
 Drinks	 Pizza	 Bread	 Frozen food and ice cream
 Off-cycle defrost	 Electric defrost	 Hot-gas defrosting system	 Manual defrost
 Ventilated	 Static	 Incorporated condensing unit	 Remote condensing unit
 Bagnomaria	 Ceramic glass	 Ice	 VSD Inverter technology
 LED lighting	 Zero C doors	 High efficiency fans	 R290 Propane refrigerant gas (R290)
 R134a R-134a - 400V/3PH/50Hz	 R404A R404A - 400V/3PH/50Hz	 R744 R744 - 400V/PH/50Hz	 Compressor hermetic reciprocating
 Hermetic scroll compressor	 Semi-hermetic reciprocating compressor	 VSD Inverter technology	 External installation
 Machinery room	 Soundproof housing	 On board condenser	 Remote condenser
 DUAL Medium & Low temperature	 Technokleen	 Thin Tech	